

SPECIFICATION FOR SATELITE DUCT TYPE

MODEL	Indoor	FCD-10	FCD-12	FCD-18	FCD-25	FCD-32	FCD-36
	Outdoor	SAC-10	SAC-12	SAC-18	SAC-25	SAC-32	SAC-36
Dry Cycle		✓	✓	✓	✓	✓	✓
Auto Restart		✓	✓	✓	✓	✓	✓
Auto Change Over		✓	✓	✓	✓	✓	✓
Comp Time Delay		✓	✓	✓	✓	✓	✓
Hot Start – Heat Pump		✓	✓	✓	✓	✓	✓
Capacity (KW)	Cooling	2700	3500	5200	7300	9300	10500
	Heating	2800	3600	5300	7500	9500	10800
Net Weight (KG)	Indoor	28	30	35	43	55	52
	Outdoor	41	45	56	72	77	88
Air Flow M³ HR	Hi	500	600	900	1200	1650	1800
	Med						
	Low						
Power Supply	V-PH-Hz	220/1/50	220/1/50	220/1/50	380/3/50	380/3/50	380/3/50
Full Load Amps	A	6	7.5	10	6	10.4	13.2
Start Amps	A	25	33	40	33	59	63
Power Input	WATT	950	970	1250	2590	3050	3550
Noise Level Outdoor	dB(A)	40	45	58	61	61	63
Max Pipe Length (M)		10	10	10	20	25	25
Max Pipe Lift (M)		5	5	5	8	8	8
Pipe Size	Liquid	3/8	3/8	3/8	3/8	3/8	3/8
	Suction	3/8	1/2	5/8	5/8	5/8	5/8
Gas Charge (KG)		0.9	1.3	1.4	2.5	2.8	3.0
Additional / Meter		60	60	70	70	70	70
Indoor Dimension	H	260	260	260	260	260	260
	W	600	600	600	600	600	600
	L	800	800	1100	1100	1250	1500
Outdoor Unit Dimension	H	590	590	590	730	730	730
	W	245	245	245	366	366	366
	L	860	860	860	950	950	950