

SPECIFICATION FOR DF UNDER CEILING & FLOOR TYPE

MODEL	Indoor	DF-10	DF-13	DF-20	DF-25	DF-32	DF-36	DF-50	DF-60
	Outdoor	SAC-10	SAC-13	SAC-20	SAC-25	SAC-32	SAC-36	SAC-50	SAC-60
Dry Cycle		✓	✓	✓	✓	✓	✓	✓	✓
Swing Function		✓	✓	✓	✓	✓	✓	✓	✓
Auto Restart		✓	✓	✓	✓	✓	✓	✓	✓
Auto Air Flow		✓	✓	✓	✓	✓	✓	✓	✓
Stop Start Timer		✓	✓	✓	✓	✓	✓	✓	✓
Auto Change Over		✓	✓	✓	✓	✓	✓	✓	✓
Comp Time Delay		✓	✓	✓	✓	✓	✓	✓	✓
Hot Start – Heat Pump		✓	✓	✓	✓	✓	✓	✓	✓
Cold Air Prevention		✓	✓	✓	✓	✓	✓	✓	✓
Capacity (KW)	Cooling	2700	3800	5900	7900	9380	10800	14800	18000
	Heating	3000	4050	6120	8210	9505	11050	15100	18215
Net Weight (KG)	Indoor	30	30	40	43	50	52	86	86
	Outdoor	41	45	58	72	84	88	105	115
Air Flow M ³ HR	Hi	500	670	1015	1300	1650	2000	2700	3350
	Med								
	Low								
Power Supply	V-PH-Hz	220/1/50	220/1/50	220/1/50	220/1/50	220/1/50	380/3/50	380/3/50	380/3/50
Full Load Amps	A	5.7	7.1	10.1	11.1	14.2	7.3	10.2	12.5
Power Input	WATT	930	1150	2105	2400	3250	4500	4520	5350
Noise Level Outdoor	dB(A)	32	33	38	44	43	48	49	50
Noise Level Indoor	dB(A)	32/34/35	32/34/35	33/35/37	35/37/39	36/38/41	36/38/41	39/42/45	40/43/46
Max Pipe Length (M)		20	25	35	55	55	80	80	80
Max Pipe Lift (M)		10	10	10	15	15	25	25	25
Pipe Size	Liquid	3/8	3/8	1/2	1/2	1/2	1/2	1/2	1/2
	Suction	1/2	1/2	5/8	5/8	5/8	5/8	3/4	3/4
Gas Charge (KG)		0.9	1.3	1.9	2.5	2.7	2.8	3.5	5.0
Additional / Meter		60	60	60	60	60	60	120	120
Indoor Dimension	H	650	650	650	650	650	650	650	650
	W	215	215	215	215	215	215	215	215
	L	854	854	1108	1108	1616	1616	1870	2369
Outdoor Unit Dimension	H	545	545	588	748	865	865	1271	1271
	W	250	250	300	300	350	350	350	350
	L	800	800	900	900	950	950	950	950