

SPECIFICATION FOR GFU UNDER CEILING & FLOOR TYPE

MODEL	Indoor	GFU-10	GFU-12	GFU-18	GFU-25	GFU-32	GFU-36	GFU-50	GFU-60
	Outdoor	SAC-10	SAC-12	SAC-18	SAC-25	SAC-32	SAC-36	SAC-50	SAC-60
Dry Cycle		✓	✓	✓	✓	✓	✓	✓	✓
Swing Function		✓	✓	✓	✓	✓	✓	✓	✓
Auto Restart		✓	✓	✓	✓	✓	✓	✓	✓
Auto Air Flow		✓	✓	✓	✓	✓	✓	✓	✓
Stop Start Timer		✓	✓	✓	✓	✓	✓	✓	✓
Auto Change Over		✓	✓	✓	✓	✓	✓	✓	✓
Comp Time Delay		✓	✓	✓	✓	✓	✓	✓	✓
Hot Start – Heat Pump		✓	✓	✓	✓	✓	✓	✓	✓
Cold Air Prevention		✓	✓	✓	✓	✓	✓	✓	✓
Capacity (KW)	Cooling	2700	3500	5200	7300	9300	10500	14800	18000
	Heating	2800	3600	5300	7500	9500	10800	15100	18100
Net Weight (KG)	Indoor	30	30	40	43	50	52	86	86
	Outdoor	42	45	56	72	77	88	100	115
Air Flow M³ HR	Hi	550	670	1015	1300	1650	2000	2700	3350
	Med								
	Low								
Power Supply	V-PH-Hz	220/1/50	220/1/50	220/1/50	220/1/50	220/1/50	380/3/50	380/3/50	380/3/50
Full Load Amps	A	4.8	5	6.5	11	12.5	10.2	11	12.5
Start Amps	A	23	25	33	54	65	63	66	74
Power Input	WATT	930	970	1250	2490	2850	3250	4400	5250
Noise Level Outdoor	dB(A)	43	45	58	61	61	63	65	65
Noise Level Indoor	dB(A)	28/32/36	30/234/35	33/35/37	35/38/31	37/39/42	41/44/47	47/50/52	48/51/54
Max Pipe Length (M)		10	10	10	20	25	25	35	40
Max Pipe Lift (M)		5	5	5	8	8	8	10	10
Pipe Size	Liquid	3/8	3/8	3/8	3/8	3/8	3/8	1/2	1/2
	Suction	1/2	1/2	5/8	5/8	5/8	5/8	3/4	3/4
Gas Charge (KG)		0.9	1.3	1.4	2.5	2.8	3.0	3.5	4.0
Additional / Meter		60	60	70	70	70	70	80	80
Indoor Dimension	H	645	645	645	645	645	645	645	645
	W	199	199	199	199	199	199	199	199
	L	996	995	995	995	995	1250	1750	1795
Outdoor Unit Dimension	H	590	590	590	730	730	730	1225	1225
	W	245	245	245	366	366	366	366	366
	L	860	860	860	950	950	950	950	950

SPECIFICATION MAY CHANGE WITHOUT PRIOR NOTICE