

SPECIFICATION FOR MK UNDER CEILING & FLOOR TYPE

MODEL	Indoor	MK-12	MK-18	MK-20	MK-25	MK-32	MK-36	MK-50	MK-60
	Outdoor	SAC-12	SAC-18	SAC-20	SAC-25	SAC-32	SAC-36	SAC-50	SAC-60
Dry Cycle		✓	✓	✓	✓	✓	✓	✓	✓
Swing Function		✓	✓	✓	✓	✓	✓	✓	✓
Auto Restart		✓	✓	✓	✓	✓	✓	✓	✓
Auto Air Flow		✓	✓	✓	✓	✓	✓	✓	✓
Stop Start Timer		✓	✓	✓	✓	✓	✓	✓	✓
Auto Change Over		✓	✓	✓	✓	✓	✓	✓	✓
Comp Time Delay		✓	✓	✓	✓	✓	✓	✓	✓
Hot Start – Heat Pump		✓	✓	✓	✓	✓	✓	✓	✓
Cold Air Prevention		✓	✓	✓	✓	✓	✓	✓	✓
Capacity (KW)	Cooling	3500	5230	5800	7300	9300	10500	14800	18000
	Heating	3650	5300	5990	7530	9480	10800	14950	18100
Net Weight (KG)	Indoor	30	40	40	43	50	52	86	86
	Outdoor	45	56	58	72	77	88	100	115
Air Flow M ³ HR	Hi	670	1015	1015	1300	1650	2000	2700	3350
Power Supply	V-PH-Hz	220/1/50	220/1/50	220/1/50	220/1/50	220/1/50	380/3/50	380/3/50	380/3/50
Full Load Amps	A	5	6.5	9.8	11	12.5	10.2	11	12.5
Start Amps	A	25	33	40	54	65	63	66	74
Power Input	WATT	970	1250	2100	2490	2850	3250	4400	5250
Noise Level Outdoor	dB(A)	45	58	58	61	61	63	65	65
Noise Level Indoor	dB(A)	32/34/35	33/35/37	33/35/38	35/38/41	37/39/42	41/44/47	47/50/52	48/51/54
Max Pipe Length (M)		10	10	20	20	25	25	35	40
Max Pipe Lift (M)		5	5	8	8	8	8	10	10
Pipe Size	Liquid	3/8	3/8	3/8	3/8	3/8	3/8	3/8	1/2
	Suction	1/2	5/8	5/8	5/8	5/8	5/8	3/4	3/4
Gas Charge (KG)		1.3	1.4	1.9	2.5	2.8	3.0	3.5	4.0
Additional / Meter		60	70	70	70	70	70	80	80
Indoor Dimension	H	650	650	650	650	680	680	680	680
	W	180	180	180	250	250	250	250	250
	L	1100	1100	1100	1100	1100	1100	1622	1622
Outdoor Unit Dimension	H	590	590	590	730	730	730	1225	1225
	W	245	300	300	366	366	366	366	366
	L	860	860	860	950	950	950	950	950