

SPECIFICATION FOR FCW – HIGH WALL UNIT

MODEL	Indoor	FCW-10	FCW-12	FCW-18	FCW-20	FCW-25	FCW-32
	Outdoor	SAC-10	SAC-12	SAC-18	SAC-20	SAC-25	SAC-32
Dry Cycle		✓	✓	✓	✓	✓	✓
Swing Function		✓	✓	✓	✓	✓	✓
Auto Restart		✓	✓	✓	✓	✓	✓
Auto Air Flow		✓	✓	✓	✓	✓	✓
Stop Start Timer		✓	✓	✓	✓	✓	✓
Auto Change Over		✓	✓	✓	✓	✓	✓
Comp Time Delay		✓	✓	✓	✓	✓	✓
Hot Start – Heat Pump		✓	✓	✓	✓	✓	✓
Cold Air Prevention		✓	✓	✓	✓	✓	✓
Capacity (KW)	Cooling	2700	3800	5550	6000	7900	9300
	Heating	2850	3960	5300	6120	8210	9480
Net Weight (KG)	Indoor	9	10	11	11	17	18
	Outdoor	41	45	56	58	72	77
Air Flow M³ HR	Hi	440	510	765	765	1020	1030
		380	420	650	650	910	920
		310	390	540	540	820	830
Power Supply	V-PH-Hz	220/1/50	220/1/50	220/1/50	220/1/50	380/3/50	380/3/50
Full Load Amps	A	5	6.5	9.8	10.1	5.0	6
Start Amps	A	25	33	40	54	32	40
Power Input	WATT	930	1150	1800	2105	2490	2850
Noise Level Outdoor	dB(A)	45	45	58	58	61	61
Noise Level Indoor	dB(A)	28/32/36	33/36/41	39/41/44	39/41/44	41/44/46	41/44/46
Max Pipe Length (M)		10	10	20	20	25	25
Max Pipe Lift (M)		5	5	8	8	8	8
Pipe Size	Liquid	3/8	3/8	3/8	3/8	3/8	3/8
	Suction	1/2	1/2	5/8	5/8	5/8	5/8
Gas Charge (KG)		0.9	1.3	1.4	1.9	2.5	2.6
Additional / Meter		60	60	70	70	70	70
Indoor Dimension	H	305	305	305	305	360	360
	W	990	990	990	990	1155	1155
	L	180	180	180	180	205	205
Outdoor Unit Dimension	H	590	590	590	590	730	730
	W	245	245	300	300	366	366
	L	860	860	860	860	950	950